Storage-media
- CFast female
- Compact Flash female
- SD female UHS-I-Card
- SD 4.0 female UHS-II-Card

FireWire
- FireWire A 6 pin male
- FireWire A 6 pin female
- FireWire B 9 pin male
- FireWire B 9 pin female
- FireWire A 4 pin male
- FireWire A 4 pin female

Multiport
- Multiport female
- USB 3.1
- USB 3.0
- USB 2.0
- eSATA
- eSATAp

Mini PCIe
- Mini PCIe male
- Mini PCIe female

Sub-D
- Serial 9 pin male
- Serial 9 pin female
- Parallel 25 pin male
- Parallel 25 pin female
- Sub-D 15 pin Gameport male
- Sub-D 15 pin Gameport female
- Sub-D 37 pin male
- Sub-D 37 pin female

M8
- M8 male
- M8 female
- waterproof

Power
- DC 1.3 x 3.5 mm male
- DC female
- DC 2.1 x 5.5 mm male
- DC female
- DIN 3 pin male
- DIN 3 pin female
- DIN 5 pin male
- DIN 5 pin female

IDE
- IDE 40 pin male
- IDE 40 pin female
- IDE 44 pin male
- IDE 44 pin female

PS/2
- Mini DIN 6 pin male
- Mini DIN 6 pin female

Displayport
- Dualport HDMI + Displayport female
- Displayport male
- Displayport female
- Mini Displayport male
- Mini Displayport female

Thunderbolt™
- Thunderbolt™ 2 male
- Thunderbolt™ 2 female
- Thunderbolt™ 3 male
- Thunderbolt™ 3 female

LIF / ZIF
- ZIF 40 pin female
- LIF 24 pin female

Mobile
- iPhone 30 pin male
- iPhone 30 pin female
- iPhone Lightning 8 pin male
- female

Graphic / Video
- RCA Video male
- RCA Video female
- S-Video male
- S-Video female
- Scart male
- Scart female
- DMS-59 male
- DMS-59 female
- VGA male
- VGA female
- VHDCI-68 male
- VHDCI-68 female
- LFH60 male
- LFH60 female

Audio
- Audio (stereo) Jack female
- Plug 3 pin 2.5 mm male
- Jack 3 pin 2.5 mm female
- Plug 4 pin 2.5 mm male
- Jack 4 pin 2.5 mm female
- Plug 3 pin 3.5 mm male
- Jack 3 pin 3.5 mm female
- Plug 4 pin 3.5 mm male
- Jack 4 pin 3.5 mm female
- Plug 5 pin 3.5 mm male
- Jack 5 pin 3.5 mm female
- Plug 3 pin 6.35 mm male
- Jack 3 pin 6.35 mm female
- TOSLINK male
- RCA male
- RCA male
- XLR male
- XLR female

RF
radio frequency technology
- N male
- N female
- F male
- F female
- TNC male
- TNC female
- RP-TNC male
- RP-TNC female
- SMA male
- SMA female
- RP-SMA male
- RP-SMA female
- SMB male
- SMB female
- SMC male
- SMC female
- MCX male
- MCX female

SATA
- SATA Pin 8 Power male
- SATA Pin 8 Power female (latching clip)
- SATA male
- SATA female
- eSATA male
- eSATA female
- eSATAp male
- eSATAp female
- eSATApd female
- Slim SATA 13 pin male
- Slim SATA 13 pin female
- Micro SATA 16 pin male
- Micro SATA 16 pin female
- SATA 22 pin male
- SATA 22 pin female
- mSATA male
- mSATA female

U.2
- U.2 SFF-8639 male
- U.2 SFF-8639 female

SATAe
- SATA Express 29 pin female
- SATA Express 18 pin male
- SATA Express 18 pin female

HDMI
- HDMI A male
- HDMI A female
- HDMI Mini-C male
- HDMI Mini-C female
- HDMI Micro-D male
- HDMI Micro-D female

DVI
- DVI-D Dual Link 24+1 male
- DVI-D Dual Link 24+1 female
- DVI-I Dual Link 24+5 male
- DVI-I Dual Link 24+5 female
- DVI-D Single Link 18+1 male
- DVI-D Single Link 18+1 female

M.2
- M.2 key B
- M.2 key M
- M.2 key B+M
- M.2 key A
- M.2 key E
- M.2 key A+E

SAS
- SAS SFF-8482 male
- SAS SFF-8482 female
- Mini SAS SFF-8088 male
- Mini SAS SFF-8088 female
- SAS SFF-8643 male
- SAS SFF-8643 female
- Mini SAS SFF-8644 male
- Mini SAS SFF-8644 female
- SAS OCuLink SFF-8611
- Slim SAS SFF-8654 male
- Slim SAS SFF-8654 female

Network
- RJ45 male
- RJ45 female
- RJ12 male
- RJ12 female
- SC Simplex male
- SC Simplex female
- LD Duplex male
- LD Duplex female
- ST Simplex male
- ST Simplex female
- SFP male
- QSFP male

USB
- EASY USB
- DUAL EASY USB
- EASY USB 2.0 Micro-B male
- EASY USB 2.0 A male
- EASY USB 2.0 A female
- 5 V
- 12 V
- 24 V
- PoweredUSB male

USB
- USB 2.0 A male
- USB 2.0 A female
- USB 2.0 B male
- USB 2.0 B female
- USB 2.0 Mini-B male
- USB 2.0 Mini-B female
- USB 2.0 Micro-B male
- USB 2.0 Micro-B female
  (MHL, SlimPort / MyDP, OTG)
- USB 2.0 9 pin pin header male
- USB 2.0 9 pin pin header female
- USB Type-C™ male
- USB Type-C™ female
- USB 3.0 A male
- USB 3.0 A female
- USB 3.0 B male
- USB 3.0 B female
- USB 3.0 Micro-B male
- USB 3.0 Micro-B female
- USB 3.0 19 pin pin header male
- USB 3.0 19 pin pin header female
- USB 3.1 key A male
- USB 3.1 key A female
- USB 3.1 key B male
- USB 3.1 key B female

FAKRA
male / female
- FAKRA A / FAKRA A
- FAKRA B / FAKRA B
- FAKRA C / FAKRA C
- FAKRA D / FAKRA D
- FAKRA E / FAKRA E
- FAKRA F / FAKRA F
- FAKRA G / FAKRA G
- FAKRA H / FAKRA H
- FAKRA I / FAKRA I
- FAKRA K / FAKRA K
- FAKRA L / FAKRA L
- FAKRA M / FAKRA M
- FAKRA N / FAKRA N
- FAKRA Z / FAKRA Z

RF
radio frequency technology
- MMCX male
- MMCX female
- MC-Card male
- CRC-9 male
- TS-9 male
- MHF (I-PEX) male
  U.FL (Hirose) compatible plug
- IEC male
- IEC female
- FME male
- FME female
- BNC male
- BNC female
- UHF male
- UHF female
- Spring connector (Banana male)
- Binding post (Banana female)

Order free of charge catalogs & flyers without password in desired quantity

www.delock.com > Infothek > Catalogs & Flyers

More detailed information about our connectors can be found at: www.delock.com > Data Library > What is

www.delock.com