

Delock Adaptor USB Type-C™ > 1 x interfață serială DB9 RS-232

Descriere scurta

Acest adaptor USB Type-C™ la serial de la Delock oferă o interfață compatibilă RS-232 DB9 pentru imprimante, instrumente de măsură, controale, dispozitive IoT etc.



ca. 25 cm

Specificatii

- Conectori:
 - 1 x USB Type-C™ tată
 - 1 x RS-232 seriale DB9 tată
- Chipset: FTDI FT232RL
- Conector serial cu piulițe
- Rată de transfer a datelor de până la 460,8 Kbps
- Semnale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Tip cablu: UL 444
- Lungime cablu fără conectori: cca 15 cm
- Culoare: negru

Cerinte de sistem

- Linux Kernel 2.6 sau superior
- Mac OS 10.13 sau superior
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC sau laptop cu un port USB Type-C™ sau Thunderbolt™ 3 liber

Pachetul contine

- USB Type-C™ la 1 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Nr. 63908


EAN: 4043619639083

Țara de origine: China

Pachet: Retail Box



Imagini



| General | |
|-------------------------------|--|
| Function: | Plug & Play |
| Specification: | RS-232 (EIA / TIA) Thunderbolt™ 3 USB Type-C™ |
| Supported operating system: | Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac OS 10.13 sau superior Linux Kernel 2.6 sau superior |
| Interface | |
| Output: | 1 x RS-232 seriale DB9, tată |
| Input: | 1 x USB Type-C™ male |
| Technical characteristics | |
| Chipset: | FTDI FT232RL |
| Data transfer rate: | up to 460,8 Kbps |
| FIFO: | 1 x 256 byte receiver 1 x 128 byte transmit |
| Data transmission: | asynchronous full duplex |
| UART: | USB to serial UART |
| Physical characteristics | |
| Cable type: | UL 444 |
| Cable diameter: | 4,4 mm |
| Cable length incl. connector: | 25 cm |
| Pin finishing: | gold-plated |
| Conductor gauge: | 28 AWG data line 24 AWG power line |
| Tipul șurubului: | #4-40 UNC |
| Shielding: | double |
| Colour: | negru |