



Delock USB Type-CTM Charger PD 85 W + Qualcomm Quick Charge 3.0 for table mounting

Description

This **USB Power Delivery (PD)** charger by Delock can be used to charge laptops with USB Type-CTM connector. It provides various voltages from 5 V to 20 V and power up to 85 Watt. In addition, 2 USB Type-A connectors with Qualcomm Quick Charge 3.0 charging technology are available for smartphones.

Qualcomm Quick Charge 3.0

The charger supports fast charging of up to 18 W with appropriately equipped smartphones.

Designed for table mounting

The charger can be inserted into an existing recess of the desk. This is a practical and space-saving solution and allows to easily charge mobile devices.

Specification

Connectors:

- 1 x USB Type-C™ female
- 2 x USB Type-A female
- 1 x DC 24 V power connector
- Output: USB Type-C[™] Power Delivery (PD): 5 V
 5 V / 9 V / 12 V / 15 V / 20 V 4.3 A
 USB Type-A Qualcomm Quick Charge 3.0 Class A: 3.6 ~ 6.5 V / 3 A, 9 V / 2 A, 12 V / 1,5 A
- Output power: max. 87 W total
- Mounting diameter: 60 mm / 80 mm
- Mounting depth: 25 mm
- Material: plastic
- Colour: white
- Dimensions: diameter ca. 9.0 cm, height ca. 2.5 cm

Power supply specification

- · Power supply with IEC-60320-C8 connector
- · Wallmount option
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output: DC 24 V / 3.74 A
 USB Type-A Qualcomm Quick Charge 3.0 Class A: 3.6 ~ 6.5 V / 2.4 A, 9 V / 2 A, 12 V / 1.5 A
- Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 11 mm

System requirements

Device with a free USB port

Package content

- USB charger for table mounting
- Adapter from 80 mm to 60 mm
- Power supply
- Power cord, length ca. 1.5 m
- Screws
- User manual



ltem no. 64065

EAN: 4043619640652

Country of origin: China

Package: Retail Box







Images

















General	
Mounting type:	in-desk
Specification:	USB Power Delivery 2.0
Interface	
connector:	1 x USB Type-C™ female
	2 x USB Type-A female
Physical characteristics	
Diameter:	90.0 mm
Height:	25 mm