



USB 3.1 Type C to Mini DisplayPort Converter with Power Delivery

No.: 43246

Description

- Adds a MiniDP port and a USB Type C power supply port to your computer
- Supports MiniDP resolutions up to 4K 3840x2160@60Hz
- Requires DisplayPort Alternate Mode support by the USB 3.1 Port/Bus
- Supports Type C power supplies up to 60W
- 2 year warranty

The Lindy USB 3.1 Type C to Mini DisplayPort Converter allows users to easily add external video capabilities to a computer featuring the USB 3.1 Type C port with support for DisplayPort Alternate Mode. USB Power Delivery of up to 60W provides power to a notebook or ultrabook via its USB Type C port whilst simultaneously using it as a video output, simply connect a compatible USB power supply to the Mini DisplayPort Converter.

With support for 4K UHD resolutions, content can be viewed with superior clarity and stunning accuracy, while the Type C connectors reversible design means a connection can be found regardless of which way the cable is inserted into the port of a laptop, notebook or Macbook. With Plug and Play installation, this converter can be installed with minimum fuss, perfect for both professional and first time users.

Technical details

Specifications

- AV Interface: USB Type C to Mini DisplayPort
- Interface Standard: DisplayPort
- Supported Bandwidth: -
- Maximum Input Resolution: 3840x2160@60Hz
- Maximum Output Resolution: 3840x2160@60Hz
- Chipset: VL100
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: PD 2.0 up to 60W (20V 3A)
- HDCP Support: HDCP 1.4 / DPCP 1.4
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x Mini DisplayPort (Female)

- Power: -

Physical Properties

- Dimensions (approx.) WxDxH: 43x40x11mm (1.69x1.57x0.43in)
- (Fixed) Cable Length: 130mm (5.12in)
- Housing Material: Plastic
- Net Weight: 0.023kg (0.05lb)
- Operating Temperature: 0°C - 45°C (32°F - 113°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)
- Humidity: 10 - 85% RH (non-condensing)
- Power Requirements: -
- Colour: White

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in)
- Gross Weight: 0.038kg (0.08lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- USB 3.1 Type C to Mini DisplayPort Converter
- Lindy Manual

Purchasing information

- No.: 43246
- EAN: 4002888432467