



# USB Type C to DVI Adapter Cable 0.5m

No.: 43255

### Description

- Converts a USB Type C port to a DVI port
- Supports DVI resolutions up to 1920x1200@60Hz
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- Plug & Play, no drivers required
- 2 Year Warranty

This Lindy USB Type C to DVI Adapter Cable allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. The DVI connector of the adapter cable can be directly connected to the DVI display - while the 0.5m cable allows for a more flexible positioning of the DVI display than when using a box converter - perfect for a simple and adaptable installation.

With support for a resolution of 1920x1200@60Hz, content can be viewed with clarity and accuracy, while the Type C connector's reversible design was developed to find a connection regardless of which way the cable is inserted into the port. The USB Type C to DVI Adapter Cable is powered by the USB Bus, therefore no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV ecosystem with minimum difficulty, ideal for both professional and first time users.

### **Technical details**

### Connectors

- Connector A: USB Type C Male
   Connector B: DVI (24+1) Male
- Housing Material: PVC
- Connector Plating: Gold
  Pin Construction: Phosphor Bronze
- Pin Plating: Gold plating
  Dimensions (approx.) WxDxH:
  - A: 12x32x6.3mm (0.47x1.26x0.25in)
  - B: 39.5x16.5x44.5mm (1.56x0.65x1.75in)

#### **Cable Construction**

- Length: 0.5m (1.64ft)
- Standard: DVI-D Single Link
- Colour: BlackType: Round
- Jacket Diameter: 4.2mm (0.17in)
- Jacket Material: PVC

- Conductor Material: Tinned Copper
  Conductor Gauge: 32+24AWG
  Shielding: Copper Braid 75%

#### **Specifications**

- Supported Bandwidth: 2.25Gbps/225MHzPower Delivery: -

- Maximum Resolution: 1920x1200@60Hz
  Nominal Attenuation: 0.1MHz-6MHz<12DB</li>
  Minumum Bend Radius: 47mm (1.85in)
  Operating Temperature: 0°C 45°C (32°F 113°F)
  Storage Temperature: -10°C 70°C (14°F 158°F)

## Miscellaneous

- Packaging Type: Polybag
  Warranty (Years): 2
  Certificated: CE, FCC, RoHS, REACH & UL

#### **Purchasing Information**

- No.: 43255EAN: 4002888432559

#### This product is also available in other lengths

- 43255 0.5m (1.64ft)
- 43256 1m (3.28ft)
- 43257 2m (6.56ft)
- 43258 3m (9.84ft)

#### © LINDY 2019