



2m Cromo USB 3.0/3.1 Cable, Type A/B

No.: 36662

Description

- Superior performance and design USB 3.0 Type A to B cable
- Supports SuperSpeed data transfer speeds up to 5Gbps
- Chrome design ABS housing, 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant, high performance tinned copper conductors
- SuperSpeed, USB 3.0, 5Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Cromo Line USB 3.0 Type A to B cables are high performance, designer connections that combine premium construction with striking connector architecture.

Cromo Line USB 3.0 cables feature triple shielded construction with tinned copper conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

The SuperSpeed protocol is supported with up to 5Gbps bandwidth to allow the rapid transfer of large data volumes.

Cromo Line USB 2.0 Type A to B cables are available in lengths from 0.5m, 1m, 2m and 3m.

Technical details

Connectors

- Connector A: USB 3.0 Type A Male
- Connector B: USB 3.0 Type B Male
- Housing Material: Chrome Plated, ABS
- Connector Plating: Gold 1µm
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold 3µm
- Dimensions (approx.) WxDxH:
 - A: 16x35x8.3mm (0.63x1.38x0.34in)
 - B: 13x37x14.3mm (0.51x1.45x0.56in)

Cable Construction

- Length: 2m (6.56ft)
- Standard: USB 3.0
- Colour: Grey
- Type: Round
- Jacket Diameter: 5.5mm (0.22in)

- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 24/28/28AWG
- Shielding: Copper Braid 65%

Specifications

- Supported Bandwidth: 5Gbps
- Maximum Resolution: -
- Nominal Attenuation:
 - 0.5-3m: 0.5MHz-7.5GHz<25DB
 - 5m: 0.5MHz~7.5GHz<32DB
- Minimum Band Radius: 55mm (2.2in)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)
- ATC Approved: -

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL

Purchasing Information

- No.: 36662
- EAN: 4002888366625

This product is also available in other lengths

- 36660 - 0.5m (1.64ft)
- 36661 - 1m (3.28ft)
- 36662 - 2m (6.56ft)
- 36663 - 3m (9.84ft)
- 36664 - 5m (16.40ft)