



## 50 x 2m USB 2.0 Type A to B Cable, Anthra Line

No.: 36688

USB Type A Male to Type B Male

### Description

- 50x professional choice USB 2.0 Type A to B, grey, cables for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts
- Double shielded cable with grey finish, corrosion resistant tinned copper conductors
- Quantity: 50, USB 2.0, 480Mbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, 50x Anthra Line USB 2.0 Type A to B, grey cables are the professional choice for high performance connections in commercial AV and IT installations.

Conveniently packaged for bulk purchasing as a collection of 50 Anthra Line USB 2.0 Type A to B, grey.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

This product features a grey finish effect on the cable.

50x USB 2.0 Type A to B Cable, Grey, Anthra Line are available in lengths from 1m, 2m and 3m

### Technical details

#### Connectors

- Connector A: USB 2.0 Type A Male
- Connector B: USB 2.0 Type B Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions (approx.) WxDxH:
  - A: 15.5x35x7.8mm (0.61x1.38x0.31in)

- B: 11.8x35x10.2mm (0.47x1.38x0.40in)

#### **Cable Construction**

- Length: 2m (6.56ft)
- Standard: USB 2.0
- Colour: Grey
- Type: Round
- Jacket Diameter: 4.4mm (0.17in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 26/28AWG
- Shielding: Aluminium Magnesium Braid

#### **Specifications**

- Supported Bandwidth: 480Mbps
- Maximum Resolution: -
- Nominal Attenuation: 5.8db/km
- Minimum Band Radius: 16mm (0.63in)
- Operating Temperature: 0°C - 60°C (32°F - 140°F)
- Storage Temperature: 0°C - 60°C (32°F - 140°F)
- ATC Approved: -

#### **Miscellaneous**

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH & UL

#### **Purchasing Information**

- No.: 36688
- EAN: 4002888366885

#### **This product is also available in other lengths**

- 36687 - 1m (3.28ft)
- 36688 - 2m (6.56ft)
- 36689 - 3m (9.84ft)