



DVI to DisplayPort Active Converter

No.: 38145

Description

- Connects a DVI-D source to a DisplayPort display or projector
- Supports resolutions up to 1920x1200@60Hz
- Can be used to add a secondary monitor for extended or mirrored desktop
- Compact dimensions for easy installation and use
- 2 year warranty

The Lindy DVI to DisplayPort converter converts signals from a DVI-D equipped source into a DisplayPort signal. It supports resolutions up to 1920x1200 and is ideal for connecting legacy PCs with a DVI-D video output to newer DisplayPort displays and projectors in offices, meeting rooms and classrooms.

The compact dimensions mean it can be easily installed in restricted spaces, allowing for tidy installation behind projectors and displays. The converter provides connectivity without the expense of having to replace legacy PCs and cabling when upgrading to modern projectors or displays.

This converter can also be used to add a secondary monitor for extended or mirrored desktop modes to increase productivity and screen real estate. Plug & play, it is quick and easy to use as it can be powered by the DVI port on the source device. In cases where power from the DVI port is insufficient, a USB port or external USB power supply can be used to provide additional power.

Technical details

Specifications

- AV Interface: DVI to DisplayPort
- Interface Standard: DVI-D, DisplayPort 1.1
- Supported Bandwidth: 4.45Gbps
- Maximum Input Resolution: 1920x1200@60Hz
- Maximum Output Resolution: 1920x1200@60Hz
- Chipset: STDP2600
- HDCP Support: HDCP 1.4
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: Powered by DVI or USB port

Connectors

- Input:
 - DVI-D Female

- USB Type A Male for optional power
- Output: DisplayPort Male

Physical properties

- Dimensions (approx.) WxDxH:
 - DP: 47.35x19.45x11.75mm (1.86x0.77x0.46in)
 - DVI: 44.9x45.3x17.3mm (1.77x1.78x0.68in)
 - USB: 47.15x15.2x8mm (1.86x0.6x0.31in)
- Cable Length: 100mm (3.94in), USB cable: 200mm (7.87in)
- Housing Material: LD PE
- Jacket Material: PVC
- Jacket Diameter: 5mm (0.2in)
- Minimum Bend Radius: 55mm (2.17in)
- Net Weight: 0.028kg (0.06lb)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -20°C - 80°C (-4°F - 176°F)
- Humidity: 20 - 90% RH (non-condensing)
- Colour: Black, red USB connector

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in)
- Gross Weight: 0.057kg (0.13lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- DVI to DisplayPort Active Converter

Purchasing Information

- No.: 38145
- EAN: 4002888381451