



## 4 Port HDMI Multi-View Switch

No.: 38150

# Description

- Integrates 4 Full HD 1080p signals for display on a single HDMI display
- Supports 4 viewing modes; Quadview, Picture & Picture, Dual Video and Standard
- Seamless switching between inputs/viewing modes
- Independent switching of audio and video signals
- 2 Year warranty

This HDMI 4x1 Multi-View Switch is a high performance video switch which allows signals from four different Full HD sources to be integrated for simultaneous display on a single monitor. Featuring four different viewing modes (Quad-View, Full Screen, Picture and Picture & Dual Video) the Multi-view switch allows for the monitoring of multiple video sources in different viewing configurations to meet the requirements of standard installations.

To ensure optimal performance in mission critical environments the Switch provides seamless switching, ensuring that there is no frame loss whilst switching between the connected source devices or between different picture modes.

Full HD 1080p resolutions are supported on both the input and output for simple integration within typical business environments, whilst the output can be down-scaled to 720p for operation with legacy displays.

Switching between audio and video channels can be completed independently using either the supplied remote control or using the front panel buttons. This independent switching allows a single audio source to be used continuously whilst switching between the connected source devices or conversely a single video source to be monitored whilst the audio source is switched.

This flexible, cost effective switch has been designed to be used in a number of different applications, such as:

- Digital Presentation
- CCTV Surveillance & Control
- Conference & Meeting Room

### **Technical details**

### **Specifications**

- AV Interface: HDMI, VGA
- Interface Standard: HDMI 1.3a
- Supports Bandwidth: 4.95 Gbps

- Maximum Resolution: 1920x1080@60Hz 4:4:4 12bit
  HDCP Support: 1.2
  Supported Audio: Audio Pass-through

- Separate Audio Ports: IR Support: CEC Support: -

- Serial Interface: -
- Special Features: PiP, PaP, Independent audio switching

#### Connectors

- Input: 4 x HDMI (Female)Output: HDMI (Female)
- Control: -
- Power: 5.5/2.1mm DC socket

## **Physical Properties**

- Dimensions WxDxH: 190x90x23mm (7.48x3.54x0.91in)
- Housing Material: Metal
- Net Weight: 0.851kg (1.88lb)
  Operating Temperature: 0°C 40°C (32°F 104°F)
  Storage Temperature: -20°C 60°C (-4°F 140°F)
  Humidity: 20 90% RH (non-condensing)
  Power Requirements: 12VDC 2A

- Colour: Black

### Miscellaneous

- Packaging Type: Carton box
  Packaging Dimensions: 200x170x60mm (7.87x6.69x2.36in)
  Gross Weight: 1.017kg (2.24lb)
  Warranty (Years): 2
  Certificated: CE, FCC, RoHS & REACH

### **Package Contents**

- HDMI 4x1 Multi-view Switch
- IR Remote control with CR2025 battery
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

## **Purchasing Information**

- No.: 38150
- EAN: 4002888381505

© LINDY 2019