



## HDMI Splitter Compact 2 Port 4K 30Hz

No.: 38157

### Description

- Supports resolutions up to 4K2K@30Hz including 1080p 3D
- Supports 7.1 channel of LPCM, Dolby TrueHD and DTS-HD Master Audio digital audio signals
- HDCP 1.4 compliant
- Supports cable distances up to 20m (10m in, 10m out)
- 2 year warranty

This compact 4K HDMI UHD splitter is capable of displaying resolutions up to 3840 x 2160, four times the resolution of HD 1080p 30Hz, future proofed for many years to come. It is also backwards compatible with previous HDMI versions supporting 1080p/1080i/720p/720i as well as 1080p 3D.

The LINDY HDMI splitters are ideal for use with source devices such as SKY HD Boxes, PlayStation 3 and 4, Xbox360, Xbox One, Blu-ray players and many more. The output ports are compatible with LED, LCD, Plasma HDTV displays as well as projectors and computer monitors.

### Note when using DVI equipped devices with this HDMI splitter:

To connect devices equipped with DVI connections, you can either use modular DVI/HDMI adapters or DVI/HDMI adapter cables. Please be aware that DVI is a "video only" interface, audio signals are not supported when using DVI devices.

### Package Contents:

HDMI Splitter, Compact  
USB Type A to micro B cable

## Technical details

### Connectors

- Input: 1 x HDMI Type A 19 Pin Male
- Output: 2 x HDMI Type A 19 Pin Male
- Power: USB Type Micro B

## **Housing**

- Material: ABS plastic
- LED Indicators: Power, Active HDMI Port
- Colour: Black
- Power Requirements: 5V DC 350mA
- Dimensions: 63 x 52 x 12mm (WxDxH)

## **Technical Information**

- Supported Bandwidth: 340MHz / 10.2Gbps
- Maximum Resolution: 4096 x 2160p 30Hz including 1080p 3D
- Maximum Colour Depth: 36 bit (12 bit per channel)
- Supported Audio: 7.1 channel of LPCM, Dolby TrueHD and DTS-HD Master Audio digital audio signals
- Infrared support: NA
- Remote control: NA
- Weight: 0.030kg
- Chipset: Lontium LT8610EX
- PSU Included: No
- Working power consumption: 1.75w
- Idle power consumption: 0.5w
- Operating Temperature: -15° - 55°C
- Storage Temperature: -20° - 80°C
- Country of Origin: China

## **Compliance**

- HDMI: V1.4
- HDCP: V1.4
- CE: Compliant
- FCC: Compliant
- RoHS 2.0: Compliant