



## 4 Port Multi AV to HDMI Presentation Switch

No.: 38270

### Description

- Multimedia solution for integrating various devices in to meeting/conference/classroom or auditorium
- Convert multiple analogue & digital inputs to a HDMI output
- Features VGA & Audio, Composite Video, Mini DisplayPort and HDMI AV inputs
- USB charging and Ethernet pass-through ports
- 2 year warranty

The LINDY Multi AV Input to HDMI Presentation Switch allows you to conveniently share content from a variety of devices to a HDMI display, such as a projector, using just a single cable.

Each of the connected devices is instantly converted and scaled to a HDMI signal, with the Presentation Switch automatically switching to use the most recently active device, making it ideal for use in class rooms, meeting/conference rooms and auditoriums.

For added convenience the Switch also features an Ethernet pass though port and a USB charging (5V 1.5A) port, handy for use in the absence of WiFi or for powering mobile devices.

In addition to the options given by the ports featured on the Switch, it is also possible to connect devices featuring different interfaces such as DisplayPort, DVI, MHL, Slimport using our range of AV converters.

The Presentation Switch can be used in conjunction with our range of long length HDMI cables and HDMI Extender's to reach even the most awkwardly located display or projector.

### Package Contents:

Multi AV Input to HDMI Presentation Switch  
Installation Bracket x 2  
Installation Screws x 8  
Desk Mount Hooks x 2  
12V 2A Multi-Country Power Supply  
LINDY Manual

### Technical details

#### Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 1.3
- Supports Bandwidth: 4.95 Gbps
- Maximum Resolution: 1920x1080@60Hz 4:4:4 8bit
- HDCP Support: 1.1
- Supported Audio: Audio Pass-through, L/R Audio via Composite
- Separate Audio Ports: Stereo (3.5mm), Composite Video & L/R audio (3 x RCA)
- IR Support: -
- CEC Support: Pass-Through
- Serial Interface: -
- Special Features: EDID Bypass

#### **Connectors**

- Input: HDMI (Female), Mini-DP (Female), VGA (Female), 3.5mm (Female), 3 x RCA (Female)
- Output: HDMI (Female), USB Type A (Female) Power Only
- Control: RJ45
- Power: 5.5/2.5mm DC socket

#### **Physical Properties**

- Dimensions WxDxH: 140x90x50mm (5.51x3.54x1.97in)
- Housing Material: Metal
- Net Weight: 0.65kg (1.43lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 10 – 85% RH (non-condensing)
- Power Requirements: 12VDC 2A
- Colour: Black

#### **Miscellaneous**

- Packaging Type: Carton box
- Packaging Dimensions: 16x22x5mm (0.63x0.87x0.2in)
- Gross Weight: 0.963kg (2.12lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

#### **Package Contents**

- Multi AV Input to HDMI Presentation Switch
- Installation Bracket x 2
- Installation Screws x 8
- Desk Mount Hooks x 2
- Multi-Country Power Supply (EU, UK, AUS & USA)
- Lindy Manual

#### **Purchasing Information**

- No.: 38270
- EAN: 4002888382700