



Presentation Switch Pro with HDBaseT Extender

No.: 38281

Description

- Professional presentation switch for connecting various source devices to a HDMI display
- Supports multi-format input resolutions up to 4K@60Hz, with additional support for HDR
- Includes 70m HDBaseT receiver with IR and RS-232 for extended switching and control
- IR, Push Button, Contacts, RS-232 and Web Gui control options for simple, flexible management of the source devices
- 2 Year warranty

The Lindy Presentation switch Pro is a versatile, professional solution for switching multiple AV source devices and outputting to a single HDMI display while providing revolutionary audio control and superior extending of the video signal via an included HDBaseT 70m receiver.

With support for input resolutions up to 4K@60Hz, and additional support for HDR, content can be seen with incredible clarity ensuring a detailed, engaging display of 4K video for educational presentations in lecture halls, corporate training or use in events where impressive content is required to captivate an audience.

This switch also features a wide range of professional audio options and connections to not only add multi-dimensional sound to create a more immersive and interactive user experience including balanced and un-balanced microphone inputs, but also provide greater control over audio processing. This allows the user to auto-mix or provide volume adjustment autonomously so specific audio sources can be amplified and background audio can be reduced when required, great for public announcements during presentations.

Source devices can be simply controlled with a variety of management options including Web Gui, IR and telnet control, providing the user with reliable, hassle-free access over source device switching, volume adjustment and the switch's OSD.

For enhanced flexibility, this switch is supplied with a high quality HDBaseT receiver to reach remote displays and projectors, at distances of up to 70m, ideal for larger lecture halls or presentation rooms. This receiver also features IR and RS-232 ports to provide control at a distance using the included remote or a PC.

Technical details

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 2.0
- Supports Bandwidth: 18Gbit/s
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8Bit

- HDCP Support: 2.2
- Supported Audio: 2-Channel LPCM
- Separate Audio Ports: Terminal Block
- IR Support: 20-60Khz
- CEC Support: Pass-through
- Serial Interface: RS232
- Special Features: EDID Management, HDBaseT Extension

Connectors

- Input: 3 x HDMI (Female), DP (Female), VGA (Female), RJ-45 (Female)
- Output: HDMI (Female), RJ-45 (Female)
- Control: Push Button, RJ-45 (IP), RS232, Terminal Block
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions (approx.) WxDxH: 220x44x150mm (8.66x1.73x5.91in)
- Housing Material: Metal
- Net Weight: 0.737kg (1.62lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20 – 90% RH (non-condensing)
- Power Requirements: 24VDC 1A
- Colour: Black

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 320x96x314mm (12.6x3.78x12.36in)
- Gross Weight: 2.133kg (4.7lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- Presentation Switch Pro
- 70m HDBaseT Receiver
- 2 x Mounting ears
- Remote Control
- 2 x IR Receiver Cable
- 2 x IR Emitter Cable
- Multi-Country Power Supply (EU, UK, AUS & USA)
- 3 RCA (Female) to VGA (Male) Cable
- Quick Installation Guide

Purchasing Information

- No.: 38281
- EAN: 4002888382816