



Switching Presentation Scaler with Table Grommet Kit

No.: 38282

Description

- Switch between HDMI, DisplayPort or VGA devices when connected to a single display
- Provide simple collaborative control over the signal with the included table grommet kit
- Supports 3 pre-set scaling options up to 4K@60Hz 4:2:0
- Embed and de-embed analogue stereo audio
- 2 Year Warranty

The Lindy Switching Presentation Scaler is a versatile, professional solution for switching and scaling up to 4 AV source devices and outputting to a single display, while providing multiple seamless control options including separate table grommets for creating a collaborative meeting room environment or engaging presentations in the workplace or in education. With dual HDMI, VGA and DisplayPort input ports, this switch can be connected to a variety of source device including PCs, media players or laptops and output to a single display or projector, and with support for resolutions up to 4K@60Hz 4:2:0, content can be viewed in highly detailed Ultra HD quality. The in-built up and down scaler function ensures the optimum video quality possible of the display is used, easily controlled via a neat push button on the unit. Any VGA source device's stereo audio can be separately embedded into HDMI, or extracted to stereo speakers to add dual channel audio to video content when audio pass-through is not available or a speaker system is preferred.

HDMI, DisplayPort and VGA table grommets are included to give a convenient extra dimension of control for the user, simply connecting directly to the source device via the required cable, a perfect solution for enhancing board room meetings or educational lectures. These grommets feature two push button options, a switching option to make a specific source device active for the display, and a black screen option, to stop showing video. Combined with IR, RS232 and push button control on the unit itself, this switch is a hassle-free yet effective solution for the user.

Technical details

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 1.4
- Supports Bandwidth: 10.2Gbps
- Maximum Resolution:
 - HDMI: 3840x2160@60Hz 4:2:0 8bit
 - VGA: 1920x1200@60Hz
- HDCP Support: 2.2

- Supported Audio:
 - HDMI Audio Pass-through
 - Stereo Analogue
- Separate Audio Ports: Analogue Audio (3-pin)
- IR Support: 38kHz
- CEC Support: Pass-through
- Serial Interface: RS232 (3-pin)
- Special Features:
 - EDID Management
 - Auto-Sensing

Connectors

- Input: 2 x HDMI Type A (Female), DisplayPort (Female), VGA (Female), 3.5mm (Female)
- Output: HDMI Type A (Female)
- Control: 3.5mm (Female), RS232 (3-pin), Table Grommet Kit (2 x HDMI Type A1 x DisplayPort, 1 x VGA)
- Power: 5.5/2.1mm

Physical Properties

- Dimensions (approx.) WxDxH: 230x23.6x100mm (9.06x0.93x3.94in)
- Housing Material: Metal
- Net Weight: 1.177kg (2.59lb)
- Operating Temperature: -10°C - 40°C (14°F - 104°F)
- Storage Temperature: -15°C - 55°C (5°F - 131°F)
- Humidity: 10-90% RH (non-condensing)
- Power Requirements: 12V 2A
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 418x82x253mm (16.46x3.23x9.96in)
- Gross Weight: 1.594kg (3.51lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- Switching Presentation Scaler
- Multi Country Power Supply (UK, EU, US & AUS Adapters)
- 2 x Mounting Brackets with 4 x Screws
- 4 x Plastic Cushions
- 10 x 3-pin Phoenix Connectors
- 1 x IR Transmitter Cable
- 2 x HDMI Table Grommets
- 1 x DisplayPort Table Grommet
- 1 x VGA Table Grommet
- 16 x Mounting Screws for Table Grommets
- Lindy Manual

Purchasing Information

- No.: 38282
- EAN: 4002888382823