



## 3 Port DisplayPort 1.2 MST Hub

No.: 38429

### Description

- Connect 3 DisplayPort displays to a DisplayPort computer or laptop
- Expand, duplicate or display independent DP signals over 3 DP monitors
- Supports resolutions up to 4K 60Hz, and audio up to 7.1CH
- Compatible with various graphics cards including AMD Eyefinity, NVIDIA Surround and Intel Collage
- 2 Year Warranty

The Lindy 3 Port DP MST Hub is an ideal solution for expanding or duplicating DisplayPort signals across 3 DisplayPort monitors. MST hubs allow for the connection of a single DP source device including computers, laptops or notebooks to 3 separate DP displays, while also providing the ability to visualise content in multiple ways. Signals can be expanded across both displays to show large scale spreadsheets, create immersive panoramic gaming experiences or eye-catching digital signage in retail. Content can also be, independently shown on either display, great for developing a productive, multi-tasking working environment, or duplicated on both displays for use in hospitality, retail or educational scenarios.

With support up to 3840x2160@60Hz 4:4:4 8bit, content can be viewed in ultra-realistic quality, ideal for applications that require a high resolution output such as graphic design, while compatibility with a variety of graphics cards including AMD Eyefinity, ensures issue free multi-screen playback.

**Please note:** This hub is not compatible with Apple products

### Technical details

#### Specification

- AV Interface: DisplayPort
- Interface Standard: DP 1.2
- Supported Bandwidth: 21Gbps
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
- HDCP Support: HDCP 1.3
- Supported Audio: Up to 7.1CH
- Separate Audio Ports: -
- CEC Support: -
- Serial Interface: -
- Special Features: -

#### Connectors

- Input: DisplayPort (Male)
- Output: 3 x DisplayPort (Female)

- Control: -
- Power: 5.5/2.5mm

#### **Physical Properties**

- Dimensions (approx.) WxDxH: 78x60x18mm (3.07x2.36x0.71in)
- Housing Material: Metal
- Net Weight: 0.095kg (0.21lb)
- Operating Temperature: 0°C - 45°C (32°F - 113°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)
- Humidity: 80 - 90% RH (non-condensing)
- Power Requirements: 5VDC 3A
- Colour: Black

#### **Miscellaneous**

- Packaging Type: Carton Box
- Packaging Dimensions: 240x145x60mm (9.45x5.71x2.36in)
- Gross Weight: 0.418kg (0.92lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, UL & REACH

#### **Package Contents**

- DisplayPort MST Hub
- Multi-country PSU (UK, EU, US & AUS)
- Lindy Manual

#### **Purchasing Information**

- No.: 38429
- EAN: 4002888384292