



## Dual Screw USB 3.1 C/C Cable 1m

No.: 41909

### Description

- 1 metre USB 3.1 Dual Screw Locking Cable
- Compliant with USB-IF Type C locking specification
- USB 3.1 Gen 2 cable supports data transfer rates up to 10Gbps
- Supports Power Delivery up to 60 Watt with E-Mark chipset
- 2 year warranty

The Lindy Dual Screw USB 3.1 Cable features two reversible USB Type C connectors, one of which is a dual screw locking connector in compliance with the USB-IF Type C locking specification. It is the perfect solution for the growing need of a secure locking mechanism in industrial environments and the ideal companion for USB devices with USB Type C locking sockets like the Lindy 4 Port USB 3.1 Gen 2 Industrial Hub (Nr. 43094).

The Lindy Dual Screw USB 3.1 Cable offers SuperSpeed+ data transfer rates of up to 10Gbps whilst supporting 60 Watt Power Delivery as well as DisplayPort Alternate Mode. It is compatible with USB 3.1 Type C and Thunderbolt 3 equipped computers.

### Technical details

#### Connectors

- Connector A: USB 3.1 Type C Male
- Connector B: USB 3.1 Type C Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold 3µm
- Dimensions (approx.) WxDxH:
  - A: 16x36x8mm (0.63x1.42x0.31in)
  - B: 19.8x35x6.4mm (0.48x0.53x1.38in)

#### Cable Construction

- Length: 1m (3.28ft)
- Standard: USB 3.1 Gen 2
- Colour: Black
- Type: Round
- Jacket Diameter: 5.2mm (0.2in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 34/26/32/30AWG

- Shielding: Copper Braid 85%

#### **Specifications**

- Supported Bandwidth: 10 Gbps
- Power Delivery: up to 60W (20V / 3A)
- Nominal Attenuation: 0.1MHz-10GHz<20DB
- Minimum Band Radius: 55mm (2.2in)
- Operating Temperature: -10°C - 55°C (-14°F - 131°F)
- Storage Temperature: -25°C - 60°C (-13°F - 140°F)

#### **Miscellaneous**

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH & UL

#### **Purchasing Information**

- No.: 41909
- EAN: 4002888419093

© LINDY 2019