



50m Hybrid USB 3.0 Cable

No.: 42701

Description

- 50m Hybrid USB 3.0 Cable
- Supports transfer rates up to 5Gbps
- Low RFI/EMI for sensitive environments
- Plug & Play installation
- 2 year warranty

The Lindy Hybrid USB 3.0 Cable extends a USB port by 50m, far longer than is possible with standard or active copper cables, whilst retaining SuperSpeed transfer rates of up to 5Gbps (backwards compatible with USB 2.0/1.1/1.0). A lighter and more flexible construction makes this cable simple to install with cable trays and through conduits, whilst low RFI/EMI ensures that the cable can be installed in the most sensitive of environments.

For added convenience the Hybrid cable is bus-powered and is supplied with a USB Micro-B cable which can be attached to a second USB port should additional power be required.

Technical details

Connectors

- Connector A: USB Type A Male
- Connector B: USB Type A Female
- Power: USB Micro-B Female
- Housing Material: Metal
- Connector Plating: Nickel 80µ
- Pin Construction: Phosphor Copper
- Pin Plating: Gold 30µ
- Dimensions (approx.) WxDxH:
 - USB A Male: 27x44x13mm (1.06x1.73x0.51in)
 - USB A Female: 26x82x14mm (1.02x3.23x0.55in)

Cable Construction

- Length: 50m (164.04ft)
- Standard: USB 3.1 Gen 1 / USB 3.0
- Colour: Black
- Type: Round
- Jacket Diameter: 3.7mm (0.15in)
- Jacket Material: TPU
- Conductor Material: 2pcs Tinned Copper Wire / 2pcs Optical Fiber
- Conductor Gauge: 22AWG / OM1
- Shielding: PVC insulation material

Specifications

- Supported Bandwidth: 5Gbps
- Nominal Attenuation: -
- Minimum Bend Radius: 50mm (1.97in)
- Maximum Tensile Load: -
- Operating Temperature: 0°C - 50°C (32°F - 122°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)
- Transmission Medium: Optical Fiber
- Transmission Technology: -

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 315x215x65mm (12.4x8.46x2.56in)
- Net Weight: 0.8kg (1.76lb)
- Gross Weight: 1.1kg (2.43lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Purchasing Information

- No.: 42701
- EAN: 4002888427012