



USB 3.0 mSATA SSD Enclosure

No.: 43117

Description

- Aluminium enclosure for mSATA SSD (not included)
- USB 3.0 / USB 3.1 Gen 1 standard with data transfer rates up to 5Gbps
- Supports SATA 1.5, 3 and 6Gbps
- Plug & Play, USB powered
- 2 year warranty

The Lindy USB 3.0 mSATA SSD Enclosure allows the use of an mSATA SSD as a portable external drive at USB 3.0 / USB 3.1 Gen 1 5Gbps speeds while also supporting the SATA 6Gbps interface to guarantee high data transfer rates. UASP support also ensures faster speeds for UASP enabled computers.

The Lindy USB 3.1 Gen 2 mSATA SSD Enclosure supports Full & Half Size mSATA SSD form factors. Easy to install, the enclosure is bus-powered so requires no external power supply.

Technical details

Specifications

- Interface: USB to mSATA
- Interface Standard: USB 3.1 Gen 1 / 3.0, SATA 3.0
- Supported Bandwidth: 5Gbps, 6Gbps
- Chipset: ASM1153e
- Compatibility: USB Type A equipped computers
- Special Features: -

Connectors

- Inputs: 1 x USB Type Micro-B (Female)
- Outputs: 1 x mSATA (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 98x40x13mm (3.86x1.57x0.51in)
- (Fixed) Cable Length: -
- Housing Material: Aluminium
- Net Weight: 0.05kg (0.11lb)
- Operating Temperature: 0°C - 70°C (32°F - 158°F)
- Storage Temperature: -40°C - 85°C (-40°F - 185°F)
- Humidity: 0 - 85% RH (non-condensing)
- Power Requirements: -

- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 140x120x40mm (5.51x4.72x1.57in)
- Gross Weight: 0.1kg (0.22lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- USB 3.1 Gen 2 M.2 SSD Enclosure
- 0.20m USB 3.1 Gen 2 Type Micro-B to C cable
- Screwdriver
- Lindy Manual

Purchasing information

- No.: 43117
- EAN: 4002888431170

© LINDY 2019