



## USB 3.0 MiniDP Docking Station

No.: 43236

### Description

- Connects to your tablet via USB Type A and Mini DisplayPort cable
- Adds 3 USB 3.0 Type A ports, an HDMI and a Gigabit Ethernet port to your tablet or ultrabook
- Conveniently attaches to your tablet/ultrabook using a stretching arm design
- Supports resolutions up to 4K Ultra HD 30Hz via MiniDP to HDMI conversion
- 2 year warranty

The Lindy USB 3.0 MiniDP Docking Station is a handy solution for connecting various peripherals to Microsoft Surface Pro devices or SurfaceBooks.

With its unique stretching arm design the USB 3.0 MiniDP Docking Station connects directly to your tablet/ultrabook, helping to reduce desk clutter whilst giving you access to a variety of common office devices. You can securely attach the Docking Station to the Kick Stand of a Surface Pro or to the screen bezel of an ultrabook (max width 32cm, depth 2.7mm).

This Docking Station has been developed to provide simple, convenient access to the most commonly used interfaces, providing access to a 3 port USB hub and Gigabit LAN via its integrated USB 3.1 Type A Cable. The docking station can also accept a Mini DisplayPort video input which is converted to a HDMI output which is capable of resolutions of up to 4K Ultra HD (3840x2160p 30Hz), making it easy to connect to a HDMI monitor.

### Technical details

#### Specifications

- Interface: USB 3.0 to USB 3.0 / RJ45 / Mini-DP / HDMI
- Interface Standard: USB 3.1 Gen 1 / 3.0, Gigabit LAN, HDMI, Mini-DisplayPort
- Supported Bandwidth: 5 Gbps, 10/100/1000Mbps
- Maximum Input Resolution: 3840x2160@30Hz
- Maximum Output Resolution: 3840x2160@30Hz
- Chipset: PS171, VL813, RTL8153
- Compatibility: USB Type A equipped computers
- Power Delivery: -
- HDCP Support: HDCP 1.3
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: With bracket for fixing on MS Surface

#### Connectors

- Inputs: 1 x USB Type A (Male)

- Outputs: 3 x USB 3.0 Type A (Female), 1 x RJ45 (female), 1 x HDMI (Female), 1 x Mini-DP (Female)
- Power: 3.5/1.35mm DC socket

#### **Physical Properties**

- Dimensions WxDxH: 255x31x33mm (10.04x1.3x1.22in)
- Housing Material: Plastic
- Net Weight: 0.16kg (0.35lb)
- Operating Temperature: -20°C - 70°C (-4°F - 158°F)
- Storage Temperature: -20°C - 85°C (-4°F - 185°F)
- Humidity: 20 - 80% RH (non-condensing)
- Power Requirements: 5VDC 2A
- Colour: Black

#### **Miscellaneous**

- Packaging Type: Carton Box
- Packaging Dimensions: 283x110x45mm (11.14x4.33x1.77in)
- Gross Weight: 0.25kg (0.55lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

#### **Package Contents**

- USB 3.1 Mini-DP Docking Station
- 0.15m DP Male to Male cable
- Lindy Manual

#### **Purchasing information**

- No.: 43236
- EAN: 4002888432368