



USB Type C to HDMI 4K60 Adapter Cable 0.5m

No.: 43260

Description

- Converts a USB Type C port to an HDMI port
- Supports HDMI resolutions up to 4K 4096x2160@60Hz (4K 60Hz only in RGB)
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- Compatible with USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- 2 Year Warranty

This Lindy USB Type C to HDMI 4K60 Adapter Cable allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. The HDMI connector of the adapter cable can be directly connected to the HDMI display - while the 0.5m cable allows for a more flexible positioning of the HDMI display than when using a box converter - perfect for a simple and adaptable installation.

With support for 4K UltraHD resolutions and HDCP 2.2, content can be viewed with superior clarity and stunning accuracy, while the Type C connectors reversible design was developed to find a connection regardless of which way the cable is inserted into the port.

The USB Type C to HDMI 4K60 Adapter Cable is powered by the USB Bus, therefore no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV ecosystem with minimum difficulty, ideal for both professional and first time users.

Technical details

Connectors

- Connector A: USB Type C Male
- Connector B: HDMI Type A Male
- Housing Material: SPCC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold plating
- Dimensions (approx.) WxDxH:
 - A: 12x23x7mm (0.47x0.91x0.28in)
 - B: 21.7x45x12mm (0.85x1.77x0.47in)

Cable Construction

- Length: 0.5m (1.64ft)
- Standard: HDMI 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 4.7mm (0.19in)

- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 32AWG
- Shielding: Copper Braid 75%

Specifications

- Supported Bandwidth: 21.6Gbps
- Power Delivery: -
- Maximum Resolution: 4096x2160@60Hz (4K 60Hz in RGB only), 2560x1440 144Hz
- Nominal Attenuation: 0.1MHz-6MHz<12DB
- Minimum Bend Radius: 47mm (1.85in)
- Operating Temperature: 0°C - 35°C (32°F - 95°F)
- Storage Temperature: 0°C - 45°C (32°F - 113°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certified: CE, FCC, RoHS, REACH & UL

Purchasing Information

- No.: 43260
- EAN: 4002888432603

This product is also available in other lengths

- 43261 - 1m (3.28ft)
- 43262 - 2m (6.56ft)
- 43263 - 3m (9.84ft)