



USB Type C to DisplayPort 4K60 Adapter Cable 0.5m

No.: 43265

Description

- Converts a USB Type C port to a DisplayPort port
- Supports DisplayPort resolutions up to 4K 3840x2160@60Hz 8bit 4:4:4
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- Plug & Play, no drivers required
- 2 Year Warranty

This Lindy USB Type C to DisplayPort 4K60 Adapter Cable allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. The DisplayPort connector of the adapter cable can be directly connected to the DisplayPort display - while the 0.5m cable allows for a more flexible positioning of the DP display than when using a box converter - perfect for a simple and adaptable installation.

With support for 4K UltraHD resolutions and HDCP 2.0, content can be viewed with superior clarity and stunning accuracy, while the Type C connectors reversible design was developed to find a connection regardless of which way the cable is inserted into the port.

The USB Type C to DisplayPort 4K60 Adapter Cable is powered by the USB Bus, therefore no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV ecosystem with minimum difficulty, ideal for both professional and first time users.

Technical details

Connectors

- Connector A: USB Type C Male
- Connector B: DisplayPort Male
- Housing Material: SPCC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold plating
- Dimensions (approx.) WxDxH:
 - A: 12x23x7mm (0.47x0.91x0.28in)
 - B: 19.5x45.5x10mm (0.77x1.79x0.39in)

Cable Construction

- Length: 0.5m (1.64ft)

- Standard: DP 1.2
- Colour: Black
- Type: Round
- Jacket Diameter: 4.7mm (0.19in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 32AWG
- Shielding: Copper Braid 75%

Specifications

- Supported Bandwidth: 21.6Gbps
- Power Delivery: -
- Maximum Resolution: 3840x2160@60Hz 8bit 4:4:4
- Nominal Attenuation: 0.1MHz-6MHz<12DB
- Minimum Bend Radius: 47mm (1.85in)
- Operating Temperature: 0°C - 35°C (32°F - 95°F)
- Storage Temperature: 0°C - 45°C (32°F - 113°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, UL

Purchasing Information

- No.: 43265
- EAN: 4002888432658

This product is also available in other lengths

- 43266 - 1m (3.28ft)
- 43267 - 2m (6.56ft)
- 43268 - 3m (9.84ft)