



USB 3.1 Type C to HDMI Converter with USB Type A port and Power Delivery

No.: 43274

Connect an HDMI display, a USB device and a Type C power supply to a single USB Type C port

Description

- Adds an HDMI port, a USB Type A port and a Type C power supply port to your computer
- Supports HDMI resolutions up to 4K 3840x2160 30Hz 8Bit RGB
- Supports USB 3.1 Gen 1 SuperSpeed 5Gbps data transfer rates
- Supports Type C power supplies up to 60W
- 2 year warranty

The Lindy USB 3.1 Type C to HDMI, USB & Power Delivery Converter allows users to maximise the functionality of a single USB 3.1 Type C port by connecting and simultaneously using an HDMI display and USB 3.1/3.0 SuperSpeed peripheral as well as a USB Type C power supply to your MacBook, ultrabook or notebook. The only requirement is that the computer supports the DisplayPort Alternate Mode.

With support for resolutions up to 3840x2160p 30Hz, the converter is ideal for use by designers and video editors.

Installation is simple as no drivers are required, while Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

Please note:

Any interruption of the power supply will cause the USB bus to reset. This is a technical limitation of USB PD 2.0.

Technical details

Specifications

- AV Interface: USB Type C to HDMI
- Interface Standard: HDMI 2.0
- Supported Bandwidth: -
- Maximum Input Resolution: 3840x2160@30Hz 8bit RGB
- Maximum Output Resolution: 3840x2160@30Hz 8bit RGB
- Chipset: PS176, VL101, VL813
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: PD 2.0 up to 60W (20V 3A)
- HDCP Support: HDCP 2.2
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x HDMI (Female), 1 x USB Type A (Female)
- Power: Bus-powered

Physical Properties

- Dimensions (approx.) WxDxH: 60x40x14mm (2.36x1.57x0.55in)
- (Fixed) Cable Length: 150mm (5.91in)
- Housing Material: Plastic
- Net Weight: 0.034kg (0.07lb)
- Operating Temperature: 0°C - 45°C (32°F - 113°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)
- Humidity: 5 - 90% RH (non-condensing)
- Power Requirements: -
- Colour: White

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in)
- Gross Weight: 0.037kg (0.08lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

Package Contents

- USB 3.1 Type C to HDMI Converter
- Lindy Manual

Purchasing information

- No.: 43274
- EAN: 4002888432740