



4 Port TosLink Audio Switch

No.: 70416

Description

- 4 Way Digital Optical Audio Switch
- Supports cables distances of up to 5m in (for each input) and 5m out
- Input ports: 4 x TosLink (Optical Fibre)
- Output port: 1 x TosLink (Optical Fibre)
- Supports uncompressed 2-channel LPCM (Linear Pulse Code Modulation) digital audio signal output
- Supports compressed 2-channel and multi-channel Dolby and DTS audio signals
- Includes 5V DC multi country power supply
- Dimensions: 95 x 85 x 35mm (WxDxH)
- 2 year warranty

Please note: TosLink cables are not included, we recommend you use cables from the LINDY or cable range

2 Way TosLink Switch, 2 Way TosLink Splitter, SPDIF to Analogue and Analogue to SPDIF converters are also available.

Technical details

Specifications

- AV Interface: TosLink
- Interface Standard: -
- Supports Bandwidth: 32 - 192kHz
- Maximum Resolution: -
- HDCP Support: -
- Supported Audio: S/PDIF, 2-Channel LPCM
- Separate Audio Ports: -
- IR Support: -
- CEC Support: -
- Serial Interface: -
- Special Features: -

Connectors

- Input: 4 x TosLink (Optical Fibre)
- Output: 1 x TosLink (Optical Fibre)
- Control: IR Remote
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions WxDxH: 85x85x34mm (3.35x3.35x1.34in)

- Housing Material: Plastic
- Net Weight: 0.095kg (0.21lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20 - 90% RH (non-condensing)
- Power Requirements: 5VDC 1A
- Colour: White

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 260x160x60mm (10.24x6.3x2.36in)
- Gross Weight: 0.44kg (0.97lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- 4 Port TosLink Audio Switch
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

Purchasing Information

- No.: 70416
- EAN: 4002888704168