



4 Port Automatic Optical Audio Switch

No.: 70437

Automatic audio switch, switches between 4 active ports

Description

- Connects four digital optical Toslink sources to a single optical Toslink input
- Automatic or manual switch function
- Input ports: 4 x Toslink (Optical Fibre)
- Output Ports: 1 x Toslink (Optical Fibre)
- 2 year warranty

The Lindy 4 Port Automatic Optical Audio Switch allows users to connect four digital optical Toslink sources to a single optical TosLink (SPDIF) input on an AV amplifier, Hi-Fi or home cinema system. The optical switch will automatically detect the live signal and switch to this channel.

Ideal for use with games consoles, HD players, set top boxes, PC's etc. and saves on wear and tear of constant plugging and unplugging of cables.

Please note: TosLink cables are not included.

Technical details

Specifications

- AV Interface: TosLink
- Interface Standard: -
- Supports Bandwidth: 32 - 96kHz
- Maximum Resolution: -
- HDCP Support: -
- Supported Audio: S/PDIF, 2-Channel LPCM
- Separate Audio Ports: -
- IR Support: -
- CEC Support: -
- Serial Interface: -
- Special Features: Automatic switching of active ports

Connectors

- Input: 4 x TosLink (Optical Fibre)
- Output: 1 x TosLink (Optical Fibre)

- Control: -
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions (approx.) WxDxH: 75x65x30mm (2.95x2.56x1.18in)
- Housing Material: Plastic
- Net Weight: 0.75kg (1.65lb)
- Operating Temperature: 0°C - 50°C (32°F - 122°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)
- Humidity: 20 - 80% RH (non-condensing)
- Power Requirements: 5VDC 1.2A
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 155x120x60mm (6.1x4.72x2.36in)
- Gross Weight: 0.293kg (0.65lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- 4 Port Automatic Optical Audio Switch
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

Purchasing Information

- No.: 70437
- EAN: 4002888704373