## ROLINE S/FTP Cable Cat.8, Solid Wire, LSOH, 100 m

**Product No.** 21.15.0005

Poline
Designed for Professionals

Manufacturer

**ROLINE** 


Manufacturer No.

21.15.0005

**EAN** (single piece)

7630049611092









Category 8, the standard for next-generation twisted-pair cabling specifications, allows the transport data up to four times faster on the same type of cabling already being used, supporting 25GBASE-T and 40GBASE-T applications for short distances (up to 30 meters) for switch-to-server connections (primarily in top-of-rack or end-of-row topologies)

- 100 meter / box
- Impedance: 100 Ohm
- Construction:
- 8 lines, solid copper wire, AWG22
- pairs shielded with aluminium foil
- complete shielding in tinned copper braid
- Colour: yellow

For a Cat.8 channel link S/FTP Cabling we recommend to use the following components:

- 21.15.0005 ROLINE S/FTP Cable, Cat.8, Solid Wire, AWG22
- 26.11.0381 ROLINE Cat.8 RJ45 Keystone, Jack, toolless
- 21.17.3086 ROLINE Cat.8 Shielded Field Connector RJ45 plug
- 21.15.1851 to 21.15.1851 ROLINE S/FTP Patch Cable Solid Cat.8, Yellow (1m to 3m)
- 21.15.1861 to 21.15.1863 ROLINE S/FTP Patch Cable Stranded Cat.8, Yellow (1m to 3m)

Technical specifications	
Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	installation cable
Colour	yellow
Length	100 m
Shield type	SFTP
Transfer quality	Cat8 / Class G
Impedance	100 Ohm
Quantity of wires	8
Conductor type	Solid wire
Colour (Cable)	yellow
Cable LSOH	Yes
Material (external cable mantle)	PVC, LSOH